

UNITED STATES PATENT APPLICATION

FOR

METHODS AND SYSTEM FOR EFFICIENT ASSOCIATION TRAVERSALS

BY

THOMAS V. JOHNSON

ZANE Z.Y. PAN

AND

CHARLES C. TING

06502.0323

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

METHODS AND SYSTEM FOR EFFICIENT ASSOCIATION TRAVERSALS

DESCRIPTION OF THE INVENTION

Field of the Invention

[001] This invention relates to Common Information Model (CIM) environments and, more particularly, to methods and systems for performing efficient association traversals.

Background of the Invention

[002] The Common Information Model (CIM) is a common data model of a schema for describing the management of information in a network environment. The model is not bound to a particular implementation and enables distributed system management to take place between management systems and applications. The CIM enables applications to be built using management data from a plurality of management systems.

[003] A CIM typically consists of two parts, a CIM specification and a CIM schema. The CIM specification describes the language, naming and mapping to other management models, while the CIM schema provides the model descriptions. The CIM schema includes a set of classes with properties and associations that are used to organize information about a managed system. The CIM schema is separated into three layers: a core model; a common model; and an extension schema.

[004] The core model contains a set of classes that are associated with a plurality of management domains. The common model is a model having a lower level than the core model, and provides base classes that are associated with certain management areas, yet not specific to a particular technology. The base classes allow for extensions into specific areas of technology. The extension schema defines technology specific extensions to the common model.

0055077 02020

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

(1) [005] The CIM is based on object-oriented modeling techniques. The Unified Modeling Language (UML) is generally used to construct an object oriented model. An exemplary model including UML representations is presented in Figure 1. As shown, a class 110 may have properties 120 and methods 130. Properties 120 are values used to represent certain characteristics of class 110, such as a unit of data. Methods 130 represent behavior characteristics of class 110.

[006] Classes may be associated with subclasses that inherit characteristics from respective classes. As shown in Figure 1, subclasses 140 and 150 have a hierarchical relationship with class 110, represented by the link 115. Thus, subclasses 140 and 150 include the characteristics of class 110, with additional characteristics uniquely defined for each subclass. A relationship between objects in a hierarchical model may also be defined between peers, such as subclasses 140 and 150. Such a relationship is represented by an association in the CIM. An association is a class that comprises two or more references. References are basically pointers to other objects and define the role each object plays in an association. An association allows the CIM schema to establish a relationship between objects without affecting the objects themselves. As shown in Figure 1, an association 160 establishes a relationship between subclasses 140 and 150. The association 160 has two references. One reference 165 is directed to subclass 150, while another reference 167 is directed to subclass 140.

[007] In the CIM model, only associations have knowledge of relationships between classes. With reference to Figure 1, only association 160 has knowledge that subclass 150 is related to subclass 140 via references 165 and 167, respectively. Subclasses 140 and 150, however, have no information indicating to either association 160 or subclass 150. Likewise, subclass 150 has no reference to either association 160 or subclass 140.

102040" 22056860

[008] While Figure 1 illustrates subclasses dependent upon a base class, other objects may be defined as well. For example, an instance may be defined that also inherits characteristics from an object it depends upon. An instance is a representation of a managed object that belongs to a particular class, or occurrence of an event. That is, an instance of a class includes real data that relates to a real world managed object. For example, suppose class 110 represents a class labeled CAR, and includes the inherent base characteristics for such a class. An instance of class 110 may represent, for example, a car driven by a particular driver. Another instance may represent a particular make of the car class 110. As described, objects such as instances are defined dynamically as the CIM schema grows. Each time an object is defined, any relationships between the newly object defined and existing objects are generally maintained in the form of an association.

[009] While the use of associations introduces a method for relating objects, a problem may occur when the relationship between the objects is requested by an application. In the CIM, the link information for an association and its referenced objects is stored with the association instance. That is, referring to Figure 1, references 165 and 167, which define the relationship between subclasses 140, 150 and association 160, are located with association 160. Therefore, in order to collect relationship information regarding subclasses 140 and 150, association 160 would have to be examined (traversed). As a result, in order to determine if there is a relationship between any two or more objects, each instance of all associations defined in a CIM schema would need to be examined to determine the existence of any related objects.

[010] In a conventional CIM schema, there is no way to recognize a relationship between two or more instances that are "separated" by intermediate associations. As an example, as shown in Figure 2, an instance of a particular class 210 is related another instance

220 by an association 215. Instance 220 has a plurality of relationships with instances 230, 240 and 250, represented by associations 222, 224 and 226, respectively. Instances 230, 240 and 250 each are separate instances of class 1, while associations 215, 222, 224 and 226 are separate instances of a class association A-1. In the conventional CIM schema depicted in Figure 2, in order to find the relationship between instance 210 and any of instances 230, 240 and 250, all associations 215, 222, 224 and 226 must be examined to identify the desired relationship. In the event a request to determine all instances associated with instance 210 is made (such as instances 220, 230, 240 and 250), all associations related to instance 210 would have to be examined to determine which objects relate to instance 210. This technique is extremely inefficient, especially in a well established schema with a complex hierarchy.

SUMMARY OF THE INVENTION

[011] It is therefore desirable to provide a method and system that enable the relationship between objects in a CIM implemented system to be realized without having to traverse each instance of an association.

[012] Methods, systems and articles of manufacture consistent with the present invention enable a CIM Object Manager (CIMOM) to create and store reverse links from an object to an association. The CIM Object Manager may then subsequently use the reverse links to efficiently determine the objects associated to a given input object, such as an instance of a class.

[013] In accordance with an aspect of the invention, clients initiate requests to create classes and instances. The requests may be sent through a network to a server node that incorporates a CIM Object Manager that performs CIM object management functions. The CIM

09895077-070201

W

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

098507.0224
T02020.205550

Object Manager processes the requests, creates the classes and instances for each class, and stores them in a CIM Object Manager repository. The CIM Object Manager creates wrappers for each instance of each class stored in the repository. The wrappers are accessible only by the CIM Object Manager, and do not interfere with object definitions. The wrappers provide knowledge to a class instance outside the object definition itself, of what relationships it participates in. In one aspect of the invention, the wrappers for each class instance point to a second level table for each association class that references the class instance. The CIM Object Manager defines association instances for each class instance that has a relationship with another class instance. In addition to creating and storing association instances in the repository, the CIM Object Manager creates references within each wrapper of a class instance. In another aspect of the invention, the wrappers for each class instance point to a second level table that contains references directed to the association class instances that reference the class instance.

[014] When the server node receives a client request for the relationship for a specific instance of a class, the CIM Object Manager accesses the reverse links stored in the wrapper of the instance associated with the request, or alternatively stored in the second level tables. The CIM Object Manager uses the reverse links to determine the relationship between the requested instance, and any other associated objects. The server node then sends the relationship information to the client.

[015] Accordingly, methods, systems and articles of manufacture consistent with the present invention enable association traversal requests to be handled without having to traverse each instance of the associations defined in an object repository.

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
. 202-408-4000

[016] Additional features of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[017] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate several embodiments of the invention and together with the description, serve to explain the principles of the invention. In the drawings:

[018] Figure 1 is a block diagram of an exemplary conventional object oriented model;

[019] Figure 2 is a block diagram of an exemplary conventional CIM hierarchy;

[020] Figure 3 is a block diagram of a CIM based network, in accordance with methods and systems consistent with features of the present invention;

[021] Figure 4 is a block diagram of the CIM Object Manager repository illustrated in Figure 3, in accordance with methods and systems consistent with features of the present invention;

[022] Figure 5A is a block diagram of an exemplary CIM hierarchy, in accordance with methods and systems consistent with features of the present invention;

[023] Figure 5B is a block diagram of wrapper tables associated with the CIM hierarchy illustrated in Figure 5A, in accordance with methods and systems consistent with features of the present invention;

[024] Figure 5C is a block diagram of an exemplary CIM hierarchy, in accordance with methods and systems consistent with features of the present invention;

09895077-00001

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

[025] Figures 5D and 5E are block diagrams of wrapper tables associated with the CIM hierarchy illustrated in Figure 5C, in accordance with methods and systems consistent with features of the present invention;

[026] Figure 6A is a block diagram of an exemplary CIM hierarchy, in accordance with methods and systems consistent with features of the present invention;

[027] Figure 6B is a block diagram of wrapper tables associated with the CIM hierarchy illustrated in Figure 6A, in accordance with methods and systems consistent with features of the present invention;

[028] Figure 6C is another block diagram of wrapper tables associated with the CIM hierarchy illustrated in Figure 6A, in accordance with methods and systems consistent with features of the present invention;

[029] Figure 6D is a block diagram of the exemplary CIM hierarchy shown in Figure 6A when another instance is added to the hierarchy, in accordance with methods and systems consistent with features of the present invention

[030] Figure 6E is a block diagram of wrapper tables associated with the CIM hierarchy illustrated in Figure 6D, in accordance with methods and systems consistent with features of the present invention;

[031] Figure 7 is an exemplary flow chart of a process performed by the CIM Object Manager associated with the creation of new instances, in accordance with methods and systems consistent with features of the present invention; and

[032] Figure 8 is a flow chart showing association traversal operations, in accordance with methods and system consistent with features of the present invention.

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

DETAILED DESCRIPTION

[033] The following description of embodiments of this invention refers to the accompanying drawings. Where appropriate, the same reference numbers in different drawings refer to the same or similar elements.

[034] In accordance with an aspect of the present invention, clients initiate CIM requests to create objects, generally, instances. The requests are received, via a network, at an object manager node incorporating a CIM Object Manager. The CIM Object Manager processes the requests and defines the objects stipulated in the client requests, and stores the definitions in a CIM Object Manager repository. Wrappers are then created for each defined object, and also are stored in the repository. The CIM Object Manager then defines associations related to the objects defined in the repository. For each association that is defined in the repository, the CIM Object Manager creates a reverse link that shows a reverse reference from each object to its respective associations. Thus, when a client initiates a relationship request associated with a particular object, the CIM Object Manager utilizes the reverse links to process the request.

[035] The requests may be generated based on an operation defined by a Web Based Enterprise Management (WBEM) specification. WBEM is an initiative that provides standard based management tools for creating a compatible computing environment for technologies like CIM and eXtensible Markup Language (XML). The requests may include a standard association traversal request. An Object Manager, among other standard management operations, also includes a predefined association traversal operation. This operation enables the Object Manager to traverse all associations of a given object.

[036] Figure 3 shows an exemplary system implementing the CIM association traversal techniques consistent with the present invention. As shown, the exemplary system comprises a JavaTM Virtual Machine (JVM) 330, a network 310 and clients 320. JVM 330

0989507.070201

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

interaction between a client 320 and management applications. CIM Object Manager 340 handles CIM based requests sent from clients 320, and manages repository 350. CIM Object Manager 340 defines classes, instances, associations, wrappers and reverse links.

[040] Repository 350 is a storage area managed by CIM Object Manager 340. Repository 350 stores the definitions of classes, instances, associations, wrappers and reverse links created by CIM Object Manager 340.

[041] Network 310 connects JVM 330 and clients 320, and may include one or more communication networks, including the Internet or any other similar network known in the art. Communication protocols used between elements connected to the network may be, but are not limited to XML, HTTP and TCP/IP.

[042] Although Figure 3 shows a network interconnecting JVM 330 and clients 320, it is understood that clients 320 and JVM 330 may be implemented in common system environment that does not require a network for the exchange of information. Furthermore, clients may include processes operating within the common system environment. Additionally, it should be understood that features and principles of the present invention need not be implemented as depicted in Figure 3. That is, the repository 350 and Object Manager 340 shown in Figure 3, are exemplary and is not intended to be limiting. For example, the repository 350 and object manager 340 need not be implemented with a virtual machine or a CIM environment, but may operate with other types of object-oriented processes that operate in a manner consistent with features and principles of the present invention.

[043] Figure 4 shows an exemplary block diagram of repository 350. As shown, repository 350 contains a plurality of defined objects 420, 450. In Figure 4, the objects represented are instances 450A-450J of a first class defined in repository 350. Instances 420A

09895077.070201

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

and 420B, for exemplary purposes, represent instances of a second class defined in repository 350. Each instance may be associated with an association 430 that represents a relationship between objects. For example, instances 420A and instance 450A have an association 430-1 establishing a relationship between these two objects. Associations 430 are considered classes in the CIM, and provide links 460 (represented as solid line arrows) to an object, such as instance 420 or instance 450. Each association class in turn may have instances defined as well. Thus, the associations 430 shown in Figure 4, may represent instances of a single association class. Links 460 point to instances and reflect a relationship between them. For example, instance 450A and instance 450F have a defined association 430-2 between them. Link 460-1 defines a reference from association 430-2 to instance 450A, and link 460-2 defines a reference from the association 430-2 to instance 450F. Repository 350 also includes wrappers 410 for each instance, 420 and 450. Wrappers 410 are locally maintained tables that are specific to an instance it "wraps." As shown in Figure 4, each wrapper (depicted as the shaded area surrounding an instance) "wraps" around an instance 420 or instance 450. These wrappers may also be referred to as instance wrappers. Wrappers 410 will be described in further detail below with respect to Figures 5A-5D and 6A-6E.

[044] Each wrapper 410 defines reverse links 440 (represented as dotted line arrows) that provide references from each instance 420, 450 to a respective association instance 430. For example, in Figure 4, the association instance 430-1 shown between instances 420B and 420A receives reverse links 440-1, 440-2 that reference the relationships from instances 420B, 420A to the association instance 430-1, respectively. It should be noted that the objects shown in Figure 4 are exemplary, and any number of objects and hierarchical relationships may be defined in the repository by CIM Object Manager 340.

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

[045] CIM Object Manager 340 establishes and manages the definitions of instances 420, 450, associations instances 430, links 460, wrappers 410 and reverse links 440. Each time an instance is created in repository 350, CIM Object Manager 340 generates associations 430 based on the hierarchical relationship associated with each defined object. In turn, whenever an association is defined, CIM Object Manager generates reverse links within each respective wrapper. Figures 5A-5D illustrate this process, in accordance with one aspect of the invention.

[046] Figure 5A shows a CIM model similar to that represented in Figure 2. That is, the model includes instances of various classes, represented by instances 510 (I-5), 520 (I-1), 530 (I-2), 540 (I-3) and 550 (I-4), and associations 515 (A-1), 522 (A-2), 524 (A-3) and 526 (A-4). Also included in the model illustrated in Figure 5A, are wrappers associated with each instance. Specifically, instance wrapper 512 is associated with instance 510 (I-5), instance wrapper 523 is associated with instance 520 (I-1), instance wrapper 532 is associated with instance 530 (I-2), instance wrapper 542 is associated with instance 540 (I-3) and instance wrapper 552 is associated with instance 550 (I-4). The wrappers shown in Figure 5A are depicted in detail in Figure 5B.

[047] Figure 5B shows repository 350 containing the wrappers, or wrapper tables, associated with each instance illustrated in Figure 5A. As shown, instance 5 wrapper table is related to wrapper 512 in Figure 5A, while the instance wrapper tables I-4 correlate to the instance wrappers 523, 532, 542 and 552 in Figure 5A, respectively. Each wrapper table includes a reference to an association instance that has been defined for its respective instance, depending upon the representation of the wrapper. That is, instance 5 wrapper table is defined for instance 510 (I-5) in Figure 5A, and any associations defined for that instance will be represented in its wrapper table. Instance 5 wrapper table includes association 515, labeled A-1, corresponding to the relationship depicted in Figure 5A. Also included in each wrapper table are

initiate a request to create a new instance I-6 of class 1. Referring to Figure 5C, CIM Object Manager 350 receives the requests and defines the new instance I-7, and stores the definition in repository 350. CIM Object Manager 340 then creates a wrapper for the newly defined instance (Step 720). A wrapper is created by creating a wrapper table for the new instance. In this case, a new wrapper table for instance 7, would be created in repository 350. The new wrapper table includes default fields to be filled relating to associations and reverse links correlated to these associations. Figure 5D shows repository 350 including newly defined wrappers, instance 6 wrapper table and instance 7 wrapper table.

[051] CIM Object Manager 340 defines an association instance 564 (A-5) between instance I-5 and instance I-7 (step 730), using the characteristics of new instance I-7. Figure 5C illustrates the new association 564 (A-5), including its links pointing to instances I-5 and I-7. Once CIM Object Manager 340 recognizes a newly defined association instance, it determines all objects the new association instance defines a relationship between. In this case, association instance A-5 establishes a relationship between instances I-5 and I-7. Accordingly, CIM Object Manager 340 defines reverse links within each instance's wrapper (Step 740). The reverse links are represented by the dotted lines pointing from wrappers 512 and 562 to association 564 (A-5) in Figure 5C.

[052] Figure 5E illustrates how the wrappers in repository 350 are modified based on the created reverse links. The addition of newly defined instance I-7, and association A-5 triggers CIM Object Manager 340 to add the reverse links to the instance 5 wrapper table. As depicted, the instance 5 wrapper table includes a reverse link showing the relationship between association A-5 and instance I-7. Furthermore, newly defined wrapper table for instance I-7 is modified to include the relationship A-5 between instance I-7 and instance I-5.

09895077.070201

[053] The process for creating and maintaining the new instance wrapper for instance I-6 in repository 350 is the same as that described for instance I-7. That is, once CIM Object Manager 340 defines an association instance A-6 between instances I-6 and I-4, a new wrapper table for the new instance I-6 is created in repository 350 and reverse links (depicted in Figure 5C as dotted lines pointing from wrappers 552 and 572 to association A-6) are defined within each instance's wrapper table. Referring to Figure 5E, the newly defined instance 6 wrapper table includes a reverse link showing the relationship between association instance A-6 and instance I-4. Furthermore, instance 4 wrapper table includes a reverse link showing the relationship between association instance A-6 and instance I-6.

[054] Accordingly, CIM Object Manager 340 dynamically adjusts repository 350 with new reverse links each time an instance of an association is created. This keeps repository 350 updated with the most recent relationships for instances defined by CIM Object Manager 340. In keeping an updated status of these relationships enable association traversals to be performed more efficiently by the CIM Object Manager 340.

[055] Although the wrapper table structure described above, provides efficient association traversals, the structure is not rigid. That is, other wrapper structures may be employed to provide traversal operations. In one aspect of the invention, the wrapper tables defined in repository 350, include pointers to secondary level association class wrapper tables. These secondary tables include each instance of a respective class association, and the reverse links to corresponding objects. Figures 6A-6E illustrate this aspect of the invention.

[056] As shown, Figure 6A shows a CIM hierarchy similar to that represented in Figure 5A. However the model illustrated in Figure 6A includes instances of several classes C-1 to C-4, and instances of several different association classes A-1 to A-3. As shown, an instance

of a first instance of class C-1 is represented by instance I-1 of class C-1 (610), while instances I-1 of C-2, I-2 of C-2 and I-3 of C-2 (622, 624 and 626, respectively), reflect instances of a second class, C-2. Additionally, individual instances of a third and fourth class are shown by I-1 of C-3 (628), and I-1 of C-4 (630). Instances 622-630 are each related to instance 610 through association instances of varying association classes 612, 614, 616, 618 and 620, respectively. Each association instance is an instance of an association class. As shown in Figure 6A, instances AC1-1, AC1-2 and AC1-3 are in association class AC1, instance AC2-1 is in association class AC2, and instance AC3-1 is in association class AC3. Although not shown in Figure 6A, a wrapper is associated with each respective class instance. These wrappers are described below with reference to Figure 6B.

[057] Figure 6B represents a wrapper table defined in repository 350 associated with class instance I-1 of C-1 (610) illustrated in Figure 6A. As shown in Figure 6B, wrapper table 632 includes a column 631 identifying association classes that have instances that are "associated" with instance I-1 of C-1 (610). Also, the wrapper table 632 includes a column 633 identifying pointers to a second wrapper table corresponding to the association classes identified in column 631. For example, column 631 of wrapper table 632 contains identifiers for association classes AC1, AC2 and AC3, and column 633 includes pointers to second level tables for these association classes 644, 646 and 648, respectively.

[058] Wrapper table 632 correlates to the relationship illustrated in Figure 6A, for instance I-1 of C-1. Referring to Figure 6A, it can be seen that instance I-1 of C-1 (610) includes references to three different association classes AC1, AC2 and AC3. Although there are several instances of association class AC1 referencing instance I-1 of C-1 (610), the wrapper table 632

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

for instance (610) only includes pointers to the association classes, not to the instances of these association classes.

[059] Referring back to Figure 6B, the second level tables 644, 646 and 648 that are referenced by column 633 include the appropriate association instances. As shown in Figure 6B, second level wrapper table AC-1 (644) includes pointers to each instance of association class AC1. Moreover, second level wrapper table 646 includes pointer to each instance of association class AC2, and second level wrapper table 648 includes pointer to each instance of association class AC3.

[060] To further explain the features and principles of the present invention, Figure 6C shows the wrapper tables associated with instance I-1 of C-3 and instance I-1 of C-4. As with the wrapper tables depicted in Figure 6B, the wrapper tables illustrated in Figure 6C correspond to the hierarchy illustrated in Figure 6A. Particularly, Figure 6C shows a wrapper table 636 including an identifier for association class AC2 and a pointer to a second level wrapper table 650 corresponding to association class AC2. Second level wrapper table 650 includes a pointer to the instance of association class AC2-1. Wrapper table 642 includes an identifier for association class AC3 and a pointer to second level wrapper table 660 corresponding to association class AC3. And, second level table 660 includes a pointer to association class instance AC3-1.

[061] To illustrate the dynamic management of the wrapper table of this aspect of the invention, Figure 6D shows new instance objects 670 and 680 added to the CIM of Figure 6A. These new objects may be added using the same client request process described for the aspect of the present invention illustrated in Figures 5A-5E and 7. That is, a client 320 may initiate a request to create a new instance of class 5 (I-1 of C-5) in repository 350. Once CIM object

102020" 22056850

manager 340 defines the new instance, an association instance is formed, based on the characteristics of instance I-4 of C-5. In this case, an new association class instance AC4-1 of association class AC4 is defined, that relates instances 680 and 622.

[062] After these objects are defined, a first level wrapper table for the affected class instances are modified to reflect the change to the CIM shown in Figure 6D. As shown in Figure 6E, the first level wrapper table 623 for class instance 622 is modified to reflect the new association class added to the CIM of Figure 6D. Particularly, first level wrapper table 623 includes identifiers 625 for association classes AC1 and AC4 corresponding to the association classes that include instances that are related to class instance 622. Also, the first level wrapper table 623 includes pointers to second level wrapper tables 627 and 629, that correspond to the association classes AC1 and AC4, respectively. Second level table 627 includes a pointer to association class instance AC1-1, and second level table 629 includes a pointer to association class instance AC4-1.

[063] As can be seen, methods and systems consistent with features of the present invention allow the first and second level wrapper tables to be used in order to maintain an updated "map" of all relationships between objects defined in repository 350. This allows specific object relationships to be efficiently provided when they are requested, by using known traversal methods and the defined wrapper tables.

[064] Figure 8 illustrates an exemplary process performed when using second level wrapper tables to perform a traversal request, consistent with features and principles of the present invention. The process begins when a traversal request is received by CIM Object Manager 340 to obtain association relations for a class instance (Step 810). Next, a defined first level wrapper table associated with the class instance designated in the request is located and

accessed (Step 820). Once located, the appropriate association classes reflected in the first level wrapper table are identified (Step 830). For each association class reflected in the first level wrapper table, a pointer corresponding to the association class is used to identify and locate the appropriate second level wrapper table (Step 840). Afterwards, the identified second level wrapper table is accessed and each instance of the association class identified in the second level table is located using defined pointer information (Step 850).

[065] The CIM Object Manager 340 accesses each association class instance identified in the second level wrapper table and references to class instances defined by these association class instances are collected (Step 855). This process repeats until there are no more association class instances identified in the second level wrapper table (Step 860). Once every instance in the second level wrapper table has been located and accessed (Step 860; NO), the first level wrapper table may be checked to determine whether there any more association classes identified in the first level wrapper table that have not been processed (Step 870). If there are more association classes, the process may be repeated by returning to Step 820. If no there are no more association classes to be processed, CIM Object Manager 340 packages the relationship information into a response for Java™ VM 330 (Step 880). Java™ VM 330 subsequently receives the packaged information and sends it to the client 320 that initiated the request (Step 890).

[066] Although Figure 8 shows the process steps associated with the first and second level tables being performed in a particular sequence, it is understood that this sequence is limiting to the present invention. That is, variations of the sequence of process steps described in Figure 8 may be implemented without departing from the features and principles of the present invention. Moreover, the process described in Figure 8 may be modified to accommodate a

09895077 070204

request to identify a particular object associated with the instance identified in the traversal request. That is, the process described in Figure 8 may be modified to accommodate a single association class traversal identified in a first level wrapper table.

[067] As described, methods and systems consistent with features of the present invention enables an efficient traversal technique to be implemented by CIM Object Manager 340 through the use of the wrappers defined in the repository. The process performed by CIM Object Manager 340 reduces the processing time and requirements for performing association traversals, by accessing the wrapper table associated with a target object. Without the wrappers, CIM Object Manager 340 would have to traverse each association to determine the objects that have relationships with the target object.

[068] The wrappers defined in repository 350 are only accessible by CIM Object Manager 340. The information within the wrappers is not directly accessible by clients 320 or any other remote system. CIM Object Manager 340 manages the definitions in repository 350, and handles CIM based requests without sharing the data stored within the wrappers. CIM Object Manager 340 may use the wrapper information to provide a response to a request, but access to the wrappers is not given to any other component. Additionally, the wrappers themselves within repository 350 are non-volatile. That is, in the event a failure occurs that affects JVM 330, the wrapper tables defined within repository 350 are not lost. In one aspect of the invention, the system implementing Java™ VM 330 may include transaction logs that record any changes to the wrappers defined in repository 350. Thus, in the event of a failure that affects Java™ VM 330, changes to the wrappers may be reinstated by using the transaction log.

[069] The foregoing description of an implementation of the invention has been presented for purposes of illustration and description. It is not exhaustive and does not limit the

[illegible]

LAW OFFICES
CAN, HENDERSON,
ABOW, GARRETT,
DUNNER, L.L.P.
O I STREET, N. W.
NGTON, DC 20005
2-408-4000

LAW OFFICES
CAN, HENDERSON,
ABOW, GARRETT,
DUNNER, L.L.P.
O I STREET, N. W.
NGTON, DC 20005
2-408-4000

LAW OFFICES
CAN, HENDERSON,
ABOW, GARRETT,
DUNNER, L.L.P.
O I STREET, N. W.
NGTON, DC 20005
2-408-4000

floppy disks, or CD-ROM; a carrier wave from the Internet or other propagation medium; or other forms of RAM or ROM. The scope of the invention is defined by the claims and their equivalents.

0989507-070201
2020/07/05 09:50

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-406-4000